



Product Description:

BESTACRYLIC SF is one-component elastic acrylic water-based coating. It creates an elastic and anti-slip coating on pitches (basketball, tennis, volleyball, etc.) from concrete or asphalt, which colours and protect from damage.

Field of application:

BESTACRYLIC SF is suitable for application on:

- Exterior pitches (basketball, tennis, volleyball, etc.)
- Concrete, cement mortar or asphalt substrates
- Roofs and courtyards of houses

Advantages

- Excellent bonding strength.
- High abrasion resistance.
- Elastic
- Easy application
- Eco-friendly

TECHNICAL INFORMATION	
Form	Liquid
Shading/Colors	White, Green (RAL 6000), Tile Red (RAL 3009)
Specific weight	1.31 ± 0.04 kg/L (23°C)
Viscosity	10000-15000 cP (23°C)
Application temperature	+5°C to +35°C
Dried on touch	1 hour
Recoating	4-8 hours
Walkability	24 hours
Maximum tensile stress (EN ISO 527-3)	>4.0 MPa
Elongation at break (EN ISO 527-3)	>120%
Elastic modulus (EN ISO 527-3)	>30 MPa
Adhesive strength (EN 1542)	2.7 N/mm ²



BEST CONSTRUCTION

CHEMICALS

Stick with Best

Method of use

Substrate condition:

- Clean the substrate from any loose pieces, as well as peeled off paints and oils. The substrate must be free of moisture and standing water.
- Prime with acrylic water-based Bestcoat PRIMER or with Bestcoat FLEX diluted 10% w/w with water depending on the nature of the substrate. In case of particularly loose substrates, prime the surface with bestacrylic SP diluted with water at a ratio of 1 to 3.

Application:

- 2-3 layers: Bestcoat FLEX undiluted. Apply with a roll, brush or airless.
- Each layer is applied crosswise, after the previous has been fully dried (after 4-8 hours depending on the ambient temperature).

Anti-slip flooring: For anti-slip surface is recommended adding quartz sand in the product prior to the application

Additional information:

All tools and application equipment must be cleaned thoroughly and immediately after their use with plenty of water.

Consumption

150 g/m² per layer on smooth substrates.

Storage

Can be stored for at least 12 months from production date in the original pails, in a cool environment protected from frost and direct sunlight

Packaging

Pails of 5 kg & 15 kg.

Colors

White, green (RAL 6000) and tile red (RAL 3009). Other colours available on request.

Disclaimer:

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.



+92 337 1439556



www.bestconstructionchemical.com



info@bestconstructionchemical.com